

# FA-300

## FLOOR DOOR 300 lb./sqft loading

### Application

- Designed for interior and exterior applications where watertightness is not required

### Product Features FA-300

- Angle frame construction with integral anchor flange is designed to be cast into concrete
- Retrofit frame design is available when unit is bolted into existing opening
- Diamond plate door panel is equipped with a flush aluminum drop handle and an automatic hold open arm

### FA-300 Floor Door Specifications:

**Material:** Aluminum door and frame; stainless steel hinges and hardware

**Door:** 1/4" aluminum diamond plate reinforced for live load of 300 lb./sq. ft.

**Frame:** Angle frame fabricated from aluminum extrusion with an integral 1" anchor flange

**Hinge:** Stainless steel butt hinges with tamperproof stainless steel bolts & nuts

**Opening Device:** Automatic hold open arm with red vinyl grip allows door panel to open to 90°, locking door in open position, and allowing for easy control when closing door panel.

When required, stainless steel compression springs can be provided to add lift assistance. Available with electrical actuators, operated by wall mounted push button switch, and remote control

**Standard Latch:** Flush aluminum drop handle with staple for padlock.

Optional: Recessed padlock provision: st/stl slamlock

**Finish:** Mill finish, with optional bituminous coating on exterior of frame

### FA-300 STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Weight per Door	
inches	mm	lbs.	kg.
24 x 24	610 x 610	45	20
24 x 30	610 x 762	53	24
24 x 36	610 x 914	59	27
30 x 30	762 x 762	59	27
30 x 48	762 x 1219	85	39
36 x 36	914 x 914	77	35
36 x 48	914 x 1219	96	44
42 x 42	1067 x 1067	98	44
48 x 48*	1219 x 1219	123	56
48 x 72*	1219 x 1829	171	78
60 x 60*	1524 x 1524	178	81

\* Double Leaf

For detailed specifications see submittal sheet

