

Product HOME-FLEX® Fitting Adapter (Female-NPT)

Project Information

Job Name: _____
Location: _____
Engineer: _____
Contractor: _____

Date Submitted: _____
Submitted by: _____
Approved by: _____
Manufacturer's Rep: _____

Installation

Must be installed in accordance with the HOME-FLEX System Design and Installation Guide and all applicable codes

Application Information

Female NPT transition fitting between HOME-FLEX® CSST and NPT thread. For use indoor, outdoor, and in concealed location applications.

Technical Data

Materials

Fitting and Retainer Ring C360 Brass
O-ring Silicone
High Temperature Gasket Non-asbestos material

Pressure Ratings

Specification Operating Pressure 25 PSIG
CSA International Evaluation Report - Max Operating Pressure 125 PSIG

Temperature Ratings

Operating Temperature Range -20°F - 200°F



Codes

ICC Codes (IFGC, IRC, IMC, IPC), UPC, NFPA (54, 58, 70, 78, 501), CAN/CSA B1491.1, NMC, CMPC, SBCCI, ICC/ANSI 2.0

Standards

ANSI LC1/CSA 6.26, UL 723/ASTM E84, ANSI Z223.1

Listings

CSA 256532, IAPMO 7660

Dimensional Information

	Size	Part Number	HOME-FLEX CSST Size	Male NPT Pipe Size	Diameter across flats (Nom. in.)	Fitting length (Nom. in.)	Weight (lbs)
	1/2"	11-435-005	1/2"	1/2"	1.15"	1.73"	0.25
	3/4"	11-435-007	3/4"	3/4"	1.45"	1.9"	0.40
	1"	11-435-010	1"	1"	1.75"	2"	0.65