



Supplies:

Requirements based on 42"/1.1 m-wide fabric.
FQ=Fat Quarter 18"x22" [45.7 cm x 55.9 cm]

	Regular	Overnight
Exterior Fabric [^]	½ yd [46 cm]	1 yd [91 cm]
Lining Fabric (includes interior pocket)	7/8 yd [79 cm]	1 ½ yds [1.4m]
Accent Fabric (front pocket, base)	FQ OR 1/3 yd [30 cm]	¾ yd [35 cm]
Fusible Woven Interfacing (Pellon SF101-20"/51 cm-wide)	2 yds [1.8 m]	2 ¼ yds [2.1 m]
Foam Stabilizer OR Fusible Fleece (by Annie's 58"/1.5 m -wide OR Pellon 987F 44"/1.2m)	½ yd [46 cm]	½ yd [46 cm]
7" x 19" piece of heavyweight interfacing for Reinforced Base, will be trimmed down (Pellon Peltex 72F or equivalent recommended)		
Zipper* for top closure	18"/45.7 cm	24"/61 cm
Cotton webbing for handles/strap (1.5"-wide/38mm)	3 ¾ yds [3.4 m]	4 yds [3.7 m]
Cotton webbing for Strap Holders (1"-wide/25mm) 5"/12.7 cm length (OR make using fabric - see instructions)		
(2) 1"/25mm -wide d-rings AND (1) 1 ½"/38mm -wide strap slider AND (2) 1 ½"/38 mm-wide swivel snaps for strap hardware		
Optional front pocket closure: one size 24 Metal Snap/or one Loxx fastener/or one 18mm magnetic snap		
Recommended Fabrics: Midweight Canvas (6-8 oz. weight) for exterior and accent fabrics. Dry oilskin/waxed twill/waxed canvas can be substituted for Exterior and/or Accent fabric. Quilting cotton for lining. See notes in instructions for substituting quilting cotton for exterior fabric/quilting. Add ½ yard low-loft cotton batting/fusible fleece/foam.		
Additional supplies + tools: Polyester thread, water-soluble pen/tailor's chalk, cutting mat, ruler, rotary cutter, size 14 or 16 denim or Microtex needle, glue or glue pen, pinking shears		
[^] ¾ yd [69 cm] required if making a single-(exterior) fabric tote (Regular size only)		
*pattern assumes fixed-length zipper and zipper tape width of 1" to 1 ¼"/2.5-3.2cm) you can substitute by-the-yard/continuous zipper, you'll need 19"/24" [48.3/61 cm] total and one pull		

← Bosal 58" Fusible Foam

← Bosal Craf-tex

← Nylon or polyester webbing can also be used.

← Use Fabric or 1.5" webbing

← Could use 1.5" d-ring or triangle ring instead of 1"

← Topstitch needle needed if using 12 wt. Topstitch Thread

← I did not use glue or pinking shears

← Use #5 Coil Zipper

☆ OPTIONAL: Add Interior Mesh Pocket. You will need 1/3 yd. Mesh & 3/4 yd. Fold-over Elastic