

Care & Maintenance:

Aeterna™ Sintered Slab

With regular maintenance and care, sintered slabs are extremely durable and can last a lifetime.

GENERAL RECOMMENDATIONS

For optimum results when using the 6 mm & 12 mm thick Aeterna™ Sintered Slabs, ensure all necessary installation conditions are in line with National applicable standards and that local building codes are met and procedures followed.

- Use professionals with demonstrated experience in laying large-format slabs.
- Ensure installation is in accordance with all local building codes.
- Ensure the installer is familiar with and following all Installation Specifications outlined in ANSI A108 and all applicable / referenced sections therein.
- Follow recommendations for all products used when installing slabs.
- Read the information in the technical guides and on the product packaging before using any product.
- Always use the recommended tools.
- Make sure that the work area is safe, clean and well lit in order to properly complete the installation and inspection required when installing large slabs.

1. MAINTENANCE

Aeterna™ Sintered Slabs have a surface that's resistant to stains and easy to maintain; to preserve these characteristics, thorough cleaning must occur as soon as installation is completed, eliminating any residues that may create a film on the surface of the product capable of retaining more dirt.

Insufficient or late removal of grout, silicone and adhesive residues may leave stains that are difficult to remove. Initial cleaning must therefore take place immediately after installation, using acid-based products, rubbing hard and rinsing well with plenty of water. This will permit the elimination of adhesive, cement, silicone residues, etc.

Care & Maintenance:

Aeterna™ Sintered Slab

Caution

- Carefully follow the instructions provided by Anatolia®. Before cleaning the surface installed, it is always best to test the cleaning agents first on a sample of the material which has not been installed, or on a small, hidden area.
- Do not use hydrochloric acid or caustic soda under any circumstances.
- Do not use products that contain hydrofluoric acid and its derivatives.
- Do not use highly concentrated potassium hydroxide or sodium hydroxide under any circumstances.

1.1. Cleaning After Installation

Use a neutral or alkaline detergent to clean away cement or grout residues. If epoxy-based grouts are used, clean away any remains as soon as the joints have been grouted, using a sponge and plenty of clean water. Clean the surface thoroughly with an alkaline detergent, following the instructions on the product label. If the surface is not cleaned immediately or there are still some epoxy remains, clean the surface using a cleaner specifically for epoxy residues. To care for the slab surface, use a neutral detergent. To clean and care for the tile/slab joints, use products specifically designed for this purpose. After the slabs have been installed, protect the newly installed floor to prevent damage until all onsite work has been completed. Wait (approximately 24 to 48 hours) for the grouting material to set before covering the newly installed slabs.

Care & Maintenance:

Aeterna™ Sintered Slab

1.2. Everyday Cleaning and Care

To remove everyday dirt, vacuum or sweep the surface regularly and then clean it with a flat mop, water and a neutral cleaner in the dilution recommended by the manufacturer. Always use a non-abrasive cloth such as a microfiber cleaning cloth when cleaning to avoid dulling your surface. Do not use cleaning wax, oil-based cleaners, ammonia, sealants or products containing acid, alkali or bleach as part of routine maintenance. Clean with warm water may be sufficient for frequent washes. After using cleaning solutions, wipe down entire area with a clean cloth or mop and clear water to remove any residue that may have been left behind. Avoid abrasive cleaning products such as scouring or steel wool pads. Use felt or rubber protective pads under furniture to prevent scratching tile/slab surfaces. Place good quality floor mats in high traffic locations and areas that are susceptible to moisture (i.e. near entrance /exit ways).

Acetone/nail polish remover, or abrasive cleaners such as Vim® Cream cleaners, Bar Keepers Friend® Soft Cleanser, or Mr. Clean® Magic Eraser® are NEVER to be used on your surface as dull spots can occur and is not covered under warranty.

Caution

All possible care should be taken to prevent the presence of material from outdoors which may cause scratches, quartz sand and other materials, since they may cause abrasion of the surface and reduce its shine.

1.3. Removing Oil and Grease

Specific cleaners are available for removing oil and grease, such as alkaline detergents or grease removers. In the case of more persistent remains, suitable products should be used. A wide range of floor cleaners can be found with a formula suited to removing these types of residues. More thorough commercial grease removers can also be used. Always test first in a hidden area before using.

Care & Maintenance:

Aeterna™ Sintered Slab

1.4. Removing Specific Stains

Slab surfaces might occasionally get stained through contact with certain substances (dyes, paint...) or as a result of spills. Everyday cleaning methods might not be sufficient in such cases, and specific procedures will be needed depending on the type of stain. Time is of the essence in removing stains and so the area in question should be cleaned as promptly as possible to prevent the substance from drying and becoming harder to remove. Staining does not indicate a flaw or defect with the material and will NOT be covered under warranty.

TYPE OF STAIN	AGENT SUBSTANCES	RECOMMENDED PRODUCTS
ENGOBE	PHOSPHORIC ACID/ CETRIMONIUM CHLORIDE	FABER- CEMENT REMOVER FILA- PH ZERO
DYE	SOLVENT- METHL CHLORITE	DNC- CHEMICAL PAINT FY FILA- NOPAINT STAR
RUST	ACID DETERGENT CETRIMONIUM CHLORIDE	PEQUINSA SC/B TENAX- RUST REMOVER FILA- PH ZERO
TRACE OF METAL	%18 HYDROCHLORIC ACID	BERILON- DK34 TENAX- BLOOSTER
NICOTINE	SOLVENT/OXIDANT HYDROJEN PEROXIDE	TENAX- BLOOSTER FILA- PS 87 PRO
CEMENT/ PLAS- TER/ LIMESCALES	PHOSPHORIC ACID/ HYDROCHLORIC ACID / MURIATRIC ACID (4%)	LITHOFIN- ZEMENT or INTENSIVE FABER- CEMENT REMOVER or DISYCOTT FILA- PH ZERO or DETERTEK
COAL	ACID DETERGENT	TENAX- BLOOSTER FILA- DETERTEK
OIL/GREASE	SOLVENT/ TOLUENE/ ALKALINE DETER- GENT / OXIDANT/ NEUTRAL DETERGENT/ PROPYLENE GLYCOL PROPYL ETHER	TENAX- BLOOSTER FABER- DEEP DEGREASER FILA- PS 87 PRO
GLUE	SOLVENT- NITRO	FABER- ALKALI CLEANER
TAR/ ASPHALT	SOLVENT/ TOLUENE/ACETONE	FABER- DEEP DEGREASER FILA- CR10 PEQUINSA REBO
IODINE	MURIATRIC ACID (4%) SODIUM HY- POCHLORIDE	TENAX- BLOOSTER FILA- PS 87 PRO
BLOOD/ TEA/COF- FEE/ KETCHUP/ MAYONNALSE	SODIUM HYPOCHLORIDE / AMONIA/ NEUTRAL DETERGENT/PROPYLENE GLYCOL PROPYL ETHER	TENAX- BLOOSTER PEQUINSA REBO FILA- PS 87 PRO or DETERTEK FABER- STAIN REMOVER
MARKER	ACETONE	ACETONE FILA- PS 87 PRO PEQUINSA- REBO

Care & Maintenance:

Aeterna™ Sintered Slab

TYPE OF STAIN	AGENT SUBSTANCES	RECOMMENDED PRODUCTS
RUBBER, TYRES	SOLVENT	FABER- FABER 30 or ALKALI CLEANER FILA- DETERTEK PRO or PS87 PRO TENAX- BRIO ACTION or BOOSTER PEQUINSA- REBO
RESIN / ENAMEL/ WAKS/ EPOXY	SOLVENT / SOLVENT	TENAX- WAKS REMOVER LITHOFIN- RESIN X FILA- CR10
BEER	AMONNIA	TENAX- BLOOSTER PEQUINSA- REBO FILA- PS 87 PRO or DETERTEK FABER- DEEP DEGREASER
LIPSTICK	ACETONE/ MURIATRIC ACID (4%)	TENAX- BLOOSTER PEQUINSA- REBO FABER- DEEP DEGREASER
WINE	AMONNIUM /BLEACH/ ALKALINE DETERGENT /SOLVENT/ METHYLGLICINE DIACETIC ACID	PEQUINSA- SC/B FABER- DEEP DEGREASER FILA- CR10
LEMON	NEUTRAL DETERGENT	FILA- CLEANER PRO FABER- TILE CLEANER or DISYCOTT TENAX- BRIOTOP
ICE CREAM	ALKALI BASED DETERGENT	FILA- PS 87 PRO FABER- DEEP DEGREASER TENAX- BLOOSTER
COLA / FRUIT JUICE	OXIDANT / NEUTRAL DETERGENT	TENAX- BRIOTOP FILA- DETERTEK FABER- DISYCOTT
SEAWEED	SODIUM HYPOCHLORIDE	FABER- COLORED STAIN REMOVER FILA- DETERTEK
FOOT PRINTS	SOLVENT/ ACETONE	FABER- DEEP DEGREASER FILA- PS 87 PRO PEQUINSA- CAUCHO
SILICONE	SOLVENT/ ACETONE	FABER- ALKALI CLEANER FILA- EPOXY CLEANER
DAILY CLEANER	AMONNIUM BASE	FABER- FLOOR CLEANER FILA- CLEANER PRO TENAX- BRIOTOP
VOMITTING	CHLORINE	TENAX- BOOSTER FABER- CEMENT REMOVER FILA- PS87 PRO

Care & Maintenance:

Aeterna™ Sintered Slab

1.5. Damages and Care

Although your Aeterna™ Sintered Slab surface is extremely durable, it is NOT indestructible. Use cutting boards to prevent scratches and be mindful around your high traffic areas like the dishwasher and the kitchen sink. Excessive force can chip and crack Aeterna™ Sintered Slabs and is not covered under warranty. The warranty does NOT cover damage caused by physical impact, chemical use, or NORMAL WEAR & TEAR OVER TIME, acts of nature, staining, scratches, or chips. It is the owner's responsibility to keep the all-slab surfaces clean and well-maintained.

It's possible to repair some scratches from the surface. When the scratches are deep on the surface, it's difficult or impossible to repair. Faber® Scratch Off Kit is recommended due to its ease of application. Be sure to follow manufacturers instructions, and always test in a hidden area.

Care & Maintenance:

Aeterna™ Sintered Slab

Countertop Comparison

Aeterna™ Sintered Slabs are a smart and safe choice for kitchen countertops. They have outstanding qualities and meet the most common parameters of durability and resistance used to evaluate materials in general.

CONDITIONS	AETERNA™ SINTERED SLAB	QUARTZ	NATURAL STONE	LAMINATES	SOLID SURFACE	STEEL
RESISTANCE TO HEAT AND HIGH TEMPERATURES	✓✓✓	✓✓	✓✓	NO	NO	✓✓✓
HYGIENIC	✓✓✓	✓✓✓	NO	NO	✓✓✓	✓✓✓
EASY TO CLEAN	✓✓✓	✓✓✓	NO	NO	✓✓	NO
NON-POROUS	✓✓✓	✓✓✓	NO	NO	✓✓✓	✓✓✓
SUITABLE FOR USE OUTDOORS	✓✓✓	NO	✓✓	NO	✓✓	✓✓
RESISTANCE TO MOLD, MILDEW AND FUNGUS	✓✓✓	✓✓✓	NO	✓✓	✓✓✓	✓✓✓
STAINPROOF	✓✓✓	✓✓	NO	✓✓	✓✓	✓✓✓
DETERGENT RESISTANCE	✓✓✓	✓✓	NO	✓✓	NO	NO
CHEMICAL RESISTANCE	✓✓✓	✓✓	NO	NO	✓✓	NO
RESISTANCE TO THERMAL SHOCK	✓✓✓	✓✓	✓✓✓	NO	✓✓	✓✓✓
FROST RESISTANCE	✓✓✓	✓✓✓	✓✓	NO	NO	✓✓✓
MOISTURE RESISTANCE	✓✓✓	✓✓✓	NO	NO	✓✓✓	✓✓✓
SCRATCH-PROOF	✓✓✓	✓✓	✓✓	NO	NO	NO
ABRASION RESISTANCE	✓✓✓	✓✓	✓✓	NO	NO	NO
UV-RESISTANCE	✓✓✓	✓✓	✓✓	NO	NO	✓✓✓

Information provided by Anatolia is to be used as a general guideline only. Always consult a professional and thoroughly review the warranty and information for any products being used. Anatolia also recommends that you test a small area prior to usage of any product to determine whether the product you are about to apply serves its intended purpose.