

DECLARATION OF PERFORMANCE

23

Declaration of Performance No: APS-DOP-01

1. Unique Identification code of the

Dry-Pressed Porcelain Tiles, With Low Water Absorption,

product-type:

Eb ≤ 0,5%

2. Product batch number:

Please see the batch number on the package.

3. Intended uses:

For Internal & External Walls and Floors.

Anatolia Porselen Seramik A.Ş.

Aliağa Organize Sanayi Bölgesi Çoraklar Mah. 5000 Sk.

4. Manufacturer:

No: 25/1 Aliağa, İzmir, 35800

Tel: +90 232 520 73 00 Fax: +90 232 520 74 00

www.anatolia.com

5. Authorised representative:

Not Relevant.

6. System of assesment and verification of

constancy of performance:

System 4

Declared Performance

Characteristics	Performance	Harmonised Technical Specification
Reaction to Fire	A1 / A1 _{FL}	
Release of dangerous substance, for - Cadmium - Lead - Other	NPD	
Breaking Strength	> 1300N for thickness ≥ 7.5 mm > 700N for thickness < 7.5 mm	
Slipperiness	TDS*	TS EN 14411:2016 EN 14411:2016
Tactility	NPD	
Bond Strength / Adhesion -Cementitious Adhesive, Type C2	> 0,5 N / mm²	
Thermal Shock Resistance	Pass.	
Durability - Internal Use: - External Use: Freeze-thaw resistance	Pass.	

^{*} Please see the technical data sheets.

The performance of the product identified in point 1 is in conformity with the declared performances. This declaration of performance is ussued in accordance with Regulation (EU) 305/2011, under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

General Manager

Muharrem UZUNATOLIA

AN TAHSIN V B. 069 074 3894

APS-DOP-01, Revision 01, Date 24.04.2025

Alosbi, Çoraklar Mah. 5000 Sk. No:25/1 Aliağa, İzmir | Telefon: +90 232 520 73 00 | www.anatolia.com