Form - Technical information

Tile collection performance based on industry standards.

	Information		
\Diamond	WATER ABSORPTION	ANSI / ISO - (%)	< 0.5%
	ABRASION RESISTANCE	ANSI / ISO	CLASS 4
50°C	SCRATCH HARDNESS	ANSI / ISO - (Mohs)	6
8/29	BREAKING STRENGTH	ANSI - (lbf) ISO - (N)	≥310 ≥1300
	SHADE VARIATION		V2 / V3 / V4
	SLIP RESISTANCE	ANSI - DCOF (WET) ISO - R VALUE	≥0.55 / R9
<u> </u>	CHEMICAL RESISTANCE	ANSI / ISO	CLASS A
చ	STAIN RESISTANCE	ANSI ISO	CLASS A CLASS 5
*	FROST RESISTANCE	ANSI / ISO	PASS

Test values are based on ANSI / ISO standards according to: ANSI A137.1 - Porcelain tile P1 Class, ISO 13006 - G - Bia Group, En 14411 - G - Bia Group. Variances in test values can occur in different production lots.

Usage recommendation

Anatolia's recommendations for suitable applications.

Usage Recommendations*		Matte Glazed Porcelain	
APPLICATION		WALL	FL00R
	RESIDENTIAL	•	•
INTERIOR	COMMERCIAL	•	•
	HEAVY COMMERCIAL	•	
EXTERIOR	RESIDENTIAL / COMMERCIAL	•	

 $^{^{\}star}$ These recommendations are not defined by ANSI/ISO standards.