










# Prima - Technical information, *Glazed Porcelain, True White Color Only*

*Tile collection performance based on industry standards.*

Technical Information <i>Glazed Porcelain, True White Color Only</i>		POLISHED	MATTE	
	WATER ABSORPTION	ANSI / ISO - (%)	< 0.5%	
	DEEP / ABRASION RESISTANCE	ANSI / ISO	4	
	SCRATCH HARDNESS	ANSI / ISO - (Mohs)	6	
	BREAKING STRENGTH	ANSI - (lbf) ISO - (N)	≥450 ≥2000	
	SHADE VARIATION		V1	
	SLIP RESISTANCE	ANSI - DCOF (WET) ISO - R VALUE	POLISHED <0.42 POLISHED R (-)	MATTE ≥0.42 MATTE R (-)
	CHEMICAL RESISTANCE	ANSI / ISO	CLASS A	
	STAIN RESISTANCE	ANSI ISO	CLASS B CLASS 4	CLASS A CLASS 5
	FROST RESISTANCE	ANSI / ISO	PASS	

Test values are based on ANSI / ISO standards according to: ANSI A137.1 - Porcelain tile P1 Class, ISO 13006 - G - Bia Group, En 14411 - G - Bia Group. Variances in test values can occur in different production lots.

## Usage recommendations










*Anatolia's recommendations for suitable applications.*

Usage Recommendations*, <i>True White</i>		POLISHED GLAZED PORCELAIN		MATTE GLAZED PORCELAIN	
APPLICATION		WALL	FLOOR	WALL	FLOOR
INTERIOR	RESIDENTIAL	•	•	•	•
	COMMERCIAL	•	•	•	•
	HEAVY COMMERCIAL	•		•	
EXTERIOR	RESIDENTIAL / COMMERCIAL	•		•	

\* These recommendations are not defined by ANSI/ISO standards.

# Prima - Technical information, *Unglazed Porcelain*

Tile collection performance based on industry standards.

Technical Information Unglazed Porcelain			POLISHED	MATTE
	WATER ABSORPTION	ANSI / ISO - (%)	< 0.5%	
	DEEP / ABRASION RESISTANCE	ANSI / ISO	135	136
	SCRATCH HARDNESS	ANSI / ISO - (Mohs)	8	9
	BREAKING STRENGTH	ANSI - (lbf) ISO - (N)	≥450 ≥2000	≥ 500 ≥ 2200
	SHADE VARIATION		V1	
	SLIP RESISTANCE	ANSI - DCOF (WET) ISO - R VALUE	POLISHED <0.42 POLISHED R (-)	MATTE ≥0.50 MATTE R (-)
	CHEMICAL RESISTANCE	ANSI / ISO	CLASS A	
	STAIN RESISTANCE	ANSI ISO	CLASS B CLASS 4	CLASS A CLASS 5
	FROST RESISTANCE	ANSI / ISO	PASS	

Test values are based on ANSI / ISO standards according to: ANSI A137.1 - Porcelain tile P1 Class, ISO 13006 - G - Bia Group, En 14411 - G - Bia Group. Variances in test values can occur in different production lots.

## Usage recommendations

*Anatolia's recommendations for suitable applications.*

Usage Recommendations*, Warm White, Mica, Smoke, Charcoal		POLISHED UNGLAZED PORCELAIN		MATTE UNGLAZED PORCELAIN	
APPLICATION		WALL	FLOOR	WALL	FLOOR
INTERIOR	RESIDENTIAL	•	•	•	•
	COMMERCIAL	•	•	•	•
	HEAVY COMMERCIAL	•	•	•	•
EXTERIOR	RESIDENTIAL / COMMERCIAL	•		•	

\* These recommendations are not defined by ANSI/ISO standards.