SDS DATE: January 2015

SECTION 1: IDENTIFICATION

PRODUCT NAME: SYNONYMS:	Element / Bliss Glass Wall Tile	
PRODUCT CODES: PRODUCT USE:	All current product references Residential & Commercial Construction Applications	
CHEMICAL NAME: CHEMICAL FAMILY: CHEMICAL FORMULA:	N/A N/A N/A	
MANUFACTURER: DIVISION: ADDRESS:	Anatolia Tile & Stone (Designer & Importer) Corporate Office 8300 Huntington Road, Vaughan, ON Canada L4L 1A5	
EMERGE NCY PHONE: CHEMTREC PHONE: OTHER CALLS:	905-771-3800	
FAX PHONE:	905-771-6300	
PREPARED BY:	Diana Vacca	

SECTION 2: HAZARD(S) IDENTIFICATION



NOTES: Not applicable for intact tiles. Excessive exposure to tile dust can cause discomfort and mechanical irritation. Long term exposure to silica dusts can lead to silicosis.

EMERGENCY OVERVIEW:

The product is not classified as hazardous according to Regulation 1272/2008 (CLP). The product is a mixture of natural occurring minerals that have been mixed with water and fired in a high temperature kiln.

MANY STAINED GLASS PRODUCTS CONTAIN METAL OXIDES. WHILE THE GLASS MATRIX CONTAINS BOUND METALS, GRINDING TO AN EXTREMELY FINE MESH SIZE CAN LIBERATE SOME METALS INTO THE AIR. GLASS CONTAINS NO FREE (OR CRYSTALLINE) SILICA; ALL COMPONENTS ARE AMORPHOUS/NON-CRYSTALLINE; CHEMICALS USED TO PRODUCE GLASS ARE NOT AVAILABLE TO THE ENVIRONMENT UNLESS ONE HEATS THE PRODUCT ABOVE 2000 °F OR GROUNDS IT TO AN EXTREMELY FINE PA RTICLE SIZE. OSHA CONSIDERS DUST AS A NUISANCE. HAND, EYE, AND OTHER BODY PARTS MAY NEED PROTECTION IF CUTTING OR REMOVING INSTALLED GLASS TILES. OTHER HAZARDS ARE DUE TO THE EXCESSIVE WEIGHT OF GLASS WHEN STACKED. USE CRATES THAT WILL NOT BREAK, AND PALLET RACKS RATED HIGHER THAN THE LOAD BEING STORED. BE AWARE OF UNSECURED STACKS OF TILE AND BREAKING CRATES. GLASS TILE PRODUCTS ARE MIXTURES OF NATURAL OCCURRING MINERALS THAT HAVE BEEN COLORED AND FIRED IN A HIGH TEMPERATURE KILN. PROPER INSTALLATION INSURES THESE PRODUCTS AS SAFE.

SDS DATE: January 2015

POTENTIAL HEALTH EFFECTS

EYES: Mechanical stress through eye rubbing if exposed to dust or airborne particulates

SKIN: Skin irritation if exposed to dust or airborne particulates

SECTION 2: HAZARD(S) IDENTIFICATION - CONTINUED

INGESTION: Potential choking hazard if exposed to airborne particulates

INHALATION: Mechanical stress from inhalation of dust or airborne particulates

ACUTE HEALTH HAZARDS: No further relevant information available.

CHRONIC HEALTH HAZARDS: No further relevant information available

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: No further relevant information available

CARCINOGENICITY

Crystalline Silica (Quartz) LD50 Rat oral > 22,500 mg/kg & LD50 Mouse oral > 15,000 mg/kg LC50 Carp > 10,000 mg/l (per 72 hr)

OSHA: Recommended that Crystalline Silica be considered a POTENTIAL occupational carcinogen

ACGIH: No information available

NTP: 9th Report: Lists Respirable Crystalline Silica as known to be a Human Carcinogen

IARC: Respirable Crystalline Silica is classified as as a Group 1 Carcinogen (carcinogenic to humans).

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT:

The product is a mixture of below natural occurring minerals that have been mixed with water and fired in a high temperature kiln. This tile contains <0.1 percent by weight each of the following elements; cadmium, zinc, chrome and other metals.

NAME	CAS NO.	<u>% WT</u>	SARA 313 REPORTABLE
Glass, SiO2-NA2O	65887-17-3	> 97.0	DSD: Not Classified CLP: Not Classified
Silicon Dioxide,* SiO2	14808-60-7	< 3.0	DSD: Not Classified
Crystalline Silica as Quartz			CLP: Not Classified

*: The composition of SiO2 may be up to 100% crystalline silica. (R): Respirable (T): Total §: Crystalline silica is normally measured as respirable dust. The OSHA standard also presents a formula for calculation of the PEL based on total dust: 30 mg/m3 / (% SiO2 + 2).

SDS DATE: January 2015

SECTION 4: FIRST AID MEASURES

Respiratory, hand and eye protection may be needed to prevent excess exposure to airborne particulates if dust is produced by cutting tiles or if dust is produced by any other operations, including removal.

EYES: Do not rub eyes in order to avoid possible cornea damage as a result of mechanical stress. Check for and remove any contact lenses. Immediately rinse contaminated eye(s) with gently running lukewarm water (saline solution is preferred) for at least 15 minutes, while holding the eyelid(s) open. In the case of an embedded particle in the eye, or if irritation occurs, consult a physician. Beyond flushing, do not attempt to remove material from the eye(s).

SECTION 4: FIRST AID MEASURED - CONTINUED

- SKIN: Carefully and gently, brush the contaminated body surfaces in order to remove all traces of glass dust. Use a brush, cloth, or gloves. Remove all contaminated clothing. Wash work clothes after each use. Wash dust-exposed skin with soap and water before eating or drinking. Contact a physician if irritation persists or later develops.
- INGESTION: Rinse out mouth and make victim drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting unless directed to do so by medical personnel; call for medical help.
- INHALATION: Move source of dust away from person, or move victim to source of fresh air. Dust in throat and nasal passages should clear spontaneously. Obtain medical attention immediately. If victim does not breath, give artificial respiration. Contact a physician immediately.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS: No further information available.

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, UPPER: Not Flammable (% BY VOLUME) LOWER: Not Flammable

FLASH POINT: No Data Available F: N/A C: N/A METHOD USED:

AUTOIGNITION TEMPERATURE: No Data Available

F: N/A

C: N/A

EXTINGUISHING MEDIA:

Suitable: Water, alcohol resistant foam, CO2, dry chemical powder Unsuitable: Water jet

SPECIAL FIRE FIGHTING PROCEDURES:

Wear self-contained breathing apparatus and full protective clothing in case of fire. Avoid breathing fire fumes. Avoid contact with sharp edges, usually generated while cutting or removing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Not explosive

HAZARDOUS DECOMPOSITION PRODUCTS:

The product is non-combustible and non-explosive and will not facilitate or sustain the combustion of other materials. Development of hazardous combustion gases or fumes are possible in the event of fire.

SDS DATE: January 2015

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

For non-emergency personnel: Keep unnecessary and unprotected personnel from entering. Wear appropriate personal protective equipment as described in Section 8. Follow the advice for safe handling and use given in Section 7.

For emergency responders: Emergency procedures are not required. Hoever, respiratory protection is needed in situations with high dust levels.

SECTION 6: ACCIDENTAL RELEASE MEASURES - CONTINUED

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP

Do not empty into drains and sewers. Keep from entering into water and ground water systems. Contain spillage where possible and safe to do so. Inform appropriate authority in case of accidental contamination of watercourses or drains.

Use dry clean up methods such as vacuum exhaust which do not generate dust formation. Never use compressed air for cleaning. If dust is formed applying a dry cleaning method, personal protective equipment must be used. Avoid inhalation of product dust and skin contact. Place the spilled material in an appropriate waste disposal container for proper disposal.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

Provide adequate ventilation. Provide local exhaust or general room ventilation to minimize dust concentrations. Avoid inhalation and contact with skin, eye and clothing.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATABILITIES:

Store in accordance with local regulations. Store in a dry, cool and well ventilated area, away from incompatible materials (see Section 10) and food and drink.

OTHER PRECAUTIONS:

No further relevant information available.

EXPOSURE GUIDELINES: Attemp to stop spillage without personal risk. Should not be released into the environment. Prevent product from entering drains.

SDS DATE: January 2015

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION



ENGINEERING CONTROLS:

Contains the following ingredients with occupational exposure limit values:

Crystalline Silica (Quartz): TWA: 0.1 mg/cubic meter (repirable dust)

VENTILATION : Provide adequate ventilation. Provide local exhaust or general room ventilation to minimize dust concentrations. The highest probability of silica exposure occurs during dry cutting. Wet cutting methods are recommended.

RESPIRATORY ROTECTION: Use FFP2 type dust mask

EYE PROTECTION: Use tight fitting safety goggles or safety glasses with side shields where dust is formed. Contact lenses may absorb irritants. Do not wear contact lenses in work areas. Have emergency eyewash station available in area where tiles are cut

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION - CONTINUED

SKIN PROTECTION: Wear dust proof protective gloves, boots, and long sleeved clothing.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None required

WORK HYGIENIC PRACTICES: Do not eat, drink or smoke when working. Wash hands and if necessary shower before breaks and after work to remove adherent product. Avoid contact with eyes and skin. After working with product, workers should wash or shower and use skin care products. Clean contaminated closting, footwear etc thoroughly before re-using them.

SECTION 9: PHYSICAL DATA

APPEARANCE:	Solid
ODOR:	Odourless
PHYSICAL STATE:	Solid
pH AS SUPPLIED: pH (Other):	No data available
BOILING POINT: F: : C'	No data available >2000
MELTING POINT:	> 2000
	No data available
VAPOR PRESSURE @ F:	(mmHg): Not applicable
C	

VAPOR DENSITY (AIR = 1): 2.35 - 2.95 g / cubic centimeter 0 F: C: SPECIFIC GRAVITY (H2O = 1): 2.5 g/cubic centimeter @ F: C: **EVAPORATION RATE:** Not applicable BASIS (=1): SOLUBILITY IN WATER: Not soluable PERCENT SOLIDS BY WEIGHT: 100% PERCENT VOLATILE: Not applicable BY WT/ BY VOL @ F:

VOLATILE ORGANIC COMPOUNDS (VOC): Not applicable

LBS/GAL

LBS/GAL

Not applicable

FILE NO.: SDS.ELEMENT.01

SDS DATE: January 2015

SECTION 10: STABILITY AND REACTIVITY DATA

Not applicable

C:

WITH WATER:

F: C:

WITHOUT WATER:

MOLECULAR WEIGHT:

VISCOSITY:

@

STABILITY: The product is STABLE under normal conditions of storage and use. Contact with incompatible materials should be avoided.

CONDITIONS TO AVOID (STABILITY): Avoid contact with acids (e.g. acetic, hydrofluoric, etc.) Glass is non-flammable. Glass will react with hydrofluoric acid producing a corrosive gas – silicon tetra fluoride.

INCOMPATIBILITY (MATERIAL TO AVOID): Acids (e.g., acetic, hydrofluoric, etc.)

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Under normal conditions of storage and use, hazardous decomposition products should not be produced. In a fire, decomposition may product toxic gases / fumes. Glass sand is not classified as a hazardous material by the criteria of the OSHA Hazard Communication Standard, Title 29, Code of Federal Regulations, Section 1910.1200.

HAZARDOUS POLYMERIZATION: Not applicable

CONDITIONS TO AVOID (POLYMERIZATION): Not applicable

SDS DATE: January 2015

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Acute: Working with broken or cut tile produces a potential for cuts to the hands and exposed body parts. Acute effects such as eye irritation may occur if associated with high dust operations such as dry cutting tile or during the removal of tile surfaces.

Chronic: Not applicable for intact tiles. Excessive exposure to tile dust cn cause discomfort and mechanical irritation. Long term exposure to silica dusts can lead to silicosis.

Crystalline Sililca (Quartz) LD50 Rat oral > 22,500 mg / kg & LD50 Mouse oral > 15,000 mg / kg LC50 Carp > 10,000 mg / l (per 72 hr)

Skin & Eye corrosion / irritation

Inhalation and potential eye exposure to eyes may cause irritation if contact is made with broken, and / or during procedures involving the cutting of tiles, and / or for operations involving the removal of installed tiles. There are no known acute effects from exposure to intact tile. Skin absorption is usually not a significant route of exposure.

Sensitization Existing lung disease may be aggravated after exposure to tile dusts. Long term exposure to silica dusts can lead to silicosis.

Genetic Toxicity No data available

Repeated Dose Toxicity No data available

Cardinogenicity

Respirable crystalline silica is classified by the International Agency for Research on Cancer (IRAC) as a Group 1 Carcinogen (carcinogenic to humans). The National Toxicology Program (9th Report) lists respirable crystalline silica as known to be a Human Carcinogen. USDOL/OSHA and NIOSH have recommended that crystalline silica be considered a potential occupational carcinogen.

Reproductive Toxicity No data available

Specific target organ Toxicitiy No data available

SECTION 12: ECOLOGICAL INFORMATION

No data available

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD:

Waste Treatment Methods Can be deposited in landfills, sent to an incineration or other appropriate means of disposal provided they meet the requirements of local laws.

Methods of Disposal The generation of waste should be avoided or minimized wherever possible. Dispose of in accordance with local regulations.

Contaminated Packaging This material and its package must be disposed of in a safe way

SDS DATE: January 2015

SECTION 14: TRANSPORT INFORMATION

RCRA HAZARD CLASS: Not applicable

SPECIAL SHIPPING INFORMATION Not Applicable

SECTION 15: REGULATORY INFORMATION

No data available

SECTION 16: PREPARATION INFORMATION

OTHER INFORMATION:

PREPARATION INFORMATION:

Date PreparedJanuary 15, 2015Revision01

DISCLAIMER: The information contained within this Safety Data Sheet is believed to be accurate and have been compiled from sources believed to be reliable. It is offered for consideration, investigation and verification. It is the users responsibility to follow the guidelines as outlined within this SDS. The user assumes all risk of use, storage and handling in compliance with applicable laws and regulations.