

# Safety Data Sheet:

## Natural Stone

FILE NO.: SDS.NATURALSTONE.01

SDS DATE: January 2024

---

### SECTION 1: IDENTIFICATION

---

PRODUCT NAME: Natural Stone (For purposes of this SDS, the term "Natural Stone Products" encompasses all types of Natural Stone products manufactured/sourced by Anatolia including granite, slate, travertine, limestone, marble, tumbled stone, and sandstone.)

SYNONYMS: Natural Stone

PRODUCT CODES: All current product references

RECOMMENDED USE: Countertop, Flooring, and Wall Application

MANUFACTURER: Distributed by Anatolia

ADDRESS: 8300 Huntington Road, Vaughan, ON Canada L4H 4Z6

EMERGENCY PHONE: 905-771-3800

PREPARED BY: Diana Vacca

This document has been prepared in accordance with the Occupational Safety and Health Administration (OSHA) Hazard Communication standard, 29 Code of Federal Regulations (CFR) 1910.1200(g), Safety Data Sheets.

---

### SECTION 2: HAZARDS IDENTIFICATION

---

Natural Stone products are mixtures of Quartz, Feldspar, and other natural occurring minerals that have been mined. The finished, Natural Stone products are odorless, stable, non-flammable, and pose no immediate hazard to health. Respiratory, hand and eye protection may be needed to prevent excess exposure to airborne particulates if dust is produced by cutting product during installation.

CLASSIFICATION OF THE CHEMICAL IN ACCORDANCE WITH PARAGRAPH (D) OF 1910.1200:

EMERGENCY OVERVIEW: Danger! Lung Injury and Cancer Hazard

GHS CLASSIFICATION (GLOBAL HARMONIZED STANDARD CLASSIFICATION):

Carcinogenicity - Category 1A (H350)

Specific target organ toxicity, single exposure; Respiratory tract irritation - Category 3 (H335)

Specific target organ toxicity, repeated exposure - Category 1A (H372)

GHS Label, Hazards and Precautionary Statements

GHS HAZARD PICTOGRAM:



CATEGORY 3  
(RESPIRATORY TRACT IRRITATION) (H335)



CATEGORY 1A  
(CARCINOGENICITY) (H372)

GHS SIGNAL WORK: Danger

GHS HAZARD STATEMENTS: (H350) May cause cancer (inhalation)  
(H335) May cause respiratory irritation  
(H372) Causes damage to organs (lung/respiratory) through prolonged or repeated exposure (inhalation)

# Safety Data Sheet:

## Natural Stone

FILE NO.: SDS.NATURALSTONE.01

SDS DATE: January 2024

---

### SECTION 2: HAZARDS IDENTIFICATION - CONTINUED

---

#### GHS PRECAUTIONARY STATEMENTS:

Do not handle until all safety precautions have been read and understood. (P202)  
Do not breathe dust/spray. (P260 + P261)  
Wash skin thoroughly after handling. (P264)  
Do not eat, drink or smoke when using this product. (P270)  
Wear protective gloves, protective clothing, eye protection, face protection. (P280)

#### HAZARDS NOT OTHERWISE CLASSIFIED:

INHALATION: Do not breathe dust. See "Potential Health Effects" in Section 11 for more details.

UNKNOWN ACUTE TOXICITY: Not applicable

---

### SECTION 3: COMPOSITION / INFORMATION OF INGREDIENTS

---

Natural Stone products are composed of Quartz, Feldspar and other naturally occurring minerals that have been mined. Natural Stone Products are mined and fabricated into various shapes, sizes, and colors. Under normal conditions these products do not release hazardous materials after installation and are not considered hazardous waste should disposal be necessary.

COMPOSITION	CAS REGISTRY NO.	% by WEIGHT (approximate)
Limestone	CAS: 1317-65-3	0-100
Crystalline silica as quartz	CAS: 14808-60-7	0-72
Feldspar	CAS: 68476-25-5	0-15
Biotite	CAS: 12001-26-2	0-5
Iron Oxide	CAS: 1345-25-1	0-2

---

### SECTION 4: FIRST AID MEASURES

---

#### DESCRIPTION OF FIRST AID MEASURES:

EYES: Immediately flush eyes with large amounts of water for at least 15 minutes if dust gets in eyes. Get medical attention if irritation persists.

SKIN: Wash thoroughly after working with Natural Stone products.

INHALATION: Remove to fresh air if exposed to large amounts of dust. Administer artificial respiration if breathing has stopped. Keep victim at rest. Call for prompt medical attention.

INGESTION: Not applicable for intact natural stone products.

#### MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED:

May cause respiratory irritation. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

#### INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

If exposed or concerned, get medical advice and attention. Have emergency eyewash station available in area where products are cut.

# Safety Data Sheet:

## Natural Stone

FILE NO.: SDS.NATURALSTONE.01

SDS DATE: January 2024

### SECTION 5: FIRE-FIGHTING MEASURES AND INFORMATION

SUITABLE EXTINGUISHING MEDIA: ABC fire extinguisher

SPECIFIC HAZARDS: Not applicable

SPECIAL FIRE FIGHTING PROCEDURES: None required

FIRE AND EXPLOSION HAZARDS: None

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES:

Do not breathe dust. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood. Use personal protection recommended in Section 8 of this SDS.

#### METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

Avoid creating excessive dust. Clean up dust with a vacuum system with a High-efficiency particulate (HEPA) air filter vacuum or damp sweeping. See Section 8 of this SDS concerning PPE information for clean-up.

### SECTION 7: HANDLING AND STORAGE

#### PRECAUTIONS FOR SAFE HANDLING:

Silica dust harmful if inhaled. Exposure to silica dust from cutting, grinding, or polishing can cause acute lung injury, silicosis, or cancer. Wear a respirator when cutting, grinding, or polishing. Use wet cutting methods and do not dry cut.

#### CONDITIONS FOR SAFE STORAGE, INCLUDING INCOMPATIBILITIES:

Do not store near acids. If natural stone products contact some acids, damage/discoloration to the surface may occur. Shelf life is unlimited.

### SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

#### 8.1. EXPOSURE TABLE:

COMPOSITION	OSHA PEL	NIOSH REL	ACGIH TLV*	UNITS
Crystalline silica as quartz	50 µg/m <sup>3</sup>	0.05 mg/m <sup>3</sup>	0.025 mg/m <sup>3</sup>	
Limestone - respirable fraction - total dust**	5 15	5 10	2 10	mg/m <sup>3</sup> mg/m <sup>3</sup>
Feldspar - respirable fraction - total dust**	N.E 15	N.E N.E	N.E N.E	mg/m <sup>3</sup> mg/m <sup>3</sup>
Biotite - respirable fraction - total dust**	5 15	15 N.E	3 N.E	mg/m <sup>3</sup> mg/m <sup>3</sup>
Iron Oxide - respirable fraction	10	5	5	mg/m <sup>3</sup>

# Safety Data Sheet:

## *Natural Stone*

FILE NO.: SDS.NATURALSTONE.01

SDS DATE: January 2024

\* 2006 Edition, respirable fraction to be determined as per Appendix D of ACGIH TLV.

\*\* Covered as particles not otherwise regulated per OSHA and particles not otherwise classified per ACGIH.

N.E. - Not established

Based on an 8hr TWA or Time Weighted Average

---

### SECTION 8.2: ENGINEERING CONTROLS / PERSONAL PROTECTION

---

VENTILATION:	Use adequate ventilation to keep exposure to dust below recommended exposure levels. Avoid inhalation of dust. The highest probability of silica exposure occurs during installation using dry cutting methods. Wet cutting methods and exposure control methods set forth in Table 1 of 29 CFR § 1926.1153 are recommended.
RESPIRATORY PROTECTION:	Use of a properly fitted NIOSH/MSHA approved particulate respirator is recommended when cutting natural stone products for installation.
EYE PROTECTION:	Use dust-proof goggles or safety glasses with side shields. Contact lenses may absorb irritants. Do not wear contact lenses in work areas.
SKIN PROTECTION:	Cotton or leather work gloves should be worn when cutting this product to minimize skin exposure to dust and/or cuts. Wash hands prior to eating, drinking, or smoking, and at the end of the work shift, after cutting operations are conducted.

---

NOTE: Personal protection information in Section 8 is based on general information for normal uses and conditions. Where special or unusual uses or conditions exist, it is suggested that the assistance of an industrial hygienist or other qualified professional be obtained.

---

---

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

APPEARANCE:	Brittle solid; color may vary
ODOR:	Odorless
ODOR THRESHOLD:	Not applicable
PH:	Not applicable
MELTING POINT:	Not available (>1000 OF)
FREEZING POINT:	Not available
BOILING POINT:	Not applicable
EVAPORATION RATE (ETHYL; ETHER = 1):	Not applicable
FLAMMABILITY:	Not applicable
UPPER/LOWER FLAMMABILITY LIMITS:	Not applicable
VAPOR PRESSURE:	Not applicable
VAPOR DENSITY (AIR = 1):	Not applicable
RELATIVE DENSITY:	Not applicable
SOLUBILITY IN WATER:	Insoluble
PARTITION COEFFICIENT: N-OCTANOL/WATER:	Not applicable

# Safety Data Sheet:

## *Natural Stone*

FILE NO.: SDS.NATURALSTONE.01

SDS DATE: January 2024

AUTO-IGNITION TEMPERATURE:	Not applicable
DECOMPOSITION TEMPERATURE:	Not applicable
VISCOSITY:	Not applicable

---

### SECTION 10: STABILITY AND REACTIVITY

---

REACTIVITY:	Not available
CHEMICAL STABILITY:	Stable in normal conditions and storage conditions.
POSSIBILITY OF HAZARDOUS REACTIONS:	Not available
CONDITIONS TO AVOID:	Avoid contact with acids (e.g., acetic, hydrofluoric, etc.)
INCOMPATIBILITY (MATERIALS TO AVOID):	Avoid contact with acids (e.g., acetic, hydrofluoric, etc.)
HAZARDOUS POLYMERIZATION:	Will not occur
HAZARDOUS DECOMPOSITION PRODUCTS:	None

---

### SECTION 11: TOXICOLOGICAL INFORMATION

---

#### POTENTIAL HEALTH EFFECTS

##### PRIMARY ROUTES OF EXPOSURE

None for intact natural stone products. Inhalation and potential exposure to eyes, hands, or other body parts if contact is made with broken products, and/or during procedures involving the cutting of products.

##### ACUTE EFFECTS CRYSTALLINE SILICA

No acute effects from exposure to intact natural stone products are known. Working with broken or cut natural stone produces a potential for cuts to the hands and exposed body parts. Acute effects such as eye irritation may occur if associated with high dust operations such as dry cutting. In very rare cases, symptoms of acute silicosis, a form of silicosis (a nodular pulmonary fibrosis) associated with exposure to respirable crystalline silica, may develop following acute exposure to extremely dusty environments caused by generation of product dust. Signs such as labored breathing and early fatigue may indicate silicosis; however, these same symptoms can arise from many other causes.

##### CHRONIC EFFECTS CRYSTALLINE SILICA

No chronic effects are known for exposure to intact natural stone products. Long-term, continual exposure to respirable crystalline silica at or above established permissible occupational exposure limits may lead to the development of silicosis, a nodular pulmonary fibrosis (NPF). NPFs are also associated with pulmonary tuberculosis, bronchitis, emphysema, and other airway diseases. This type of chronic exposure to silica dust may also result in the development of autoimmune disorders, chronic renal disease, and other adverse health effects. Recent epidemiologic studies demonstrate that workers exposed to elevated silica concentrations have a significant risk of developing chronic silicosis. Signs such as labored breathing and early fatigue may indicate silicosis; however, these same symptoms can also arise from many other causes.

##### POTENTIAL ADVERSE INTERACTIONS

Silicosis may be complicated by severe mycobacterial or fungal infections and result in tuberculosis (TB). Epidemiologic studies have established that silicosis is a risk factor for developing TB. Any existing respiratory or pulmonary diseases may be complicated by exposure to respirable crystalline silica. Smoking may increase the risk of adverse effects if done in conjunction with occupational exposure to silica dust at or above permissible exposure limits.

# Safety Data Sheet:

## *Natural Stone*

FILE NO.: SDS.NATURALSTONE.01

SDS DATE: January 2024

### CARCINOGEN STATUS

Respirable crystalline silica is classified by the International Agency for Research on Cancer (IARC) as a Group I Carcinogen (carcinogenic to humans). The National Toxicology Program (9th Report) lists respirable crystalline silica as "Known to be a Human Carcinogen." USDOL/OSHA lists crystalline silica in the OSHA Hazard Communication Carcinogen list.

### ACUTE TOXICITY

Not applicable

### OVERVIEW OF ANIMAL TESTING

Short term experimental studies of rats have found that intratracheal instillation of quartz particles leads to the formation of discrete silicotic nodules in rats, mice and hamsters.

### ORAL (SILICA) LETHALITY

LD50 Rat oral >22,500 mg/kg LD50  
Mouse oral >15,000 mg/kg  
LC50 Carp >10,000 mg/l (per 72 hr.)

---

### SECTION 12: ECOLOGICAL INFORMATION

---

No information available at this time.

---

### SECTION 13: DISPOSAL CONSIDERATIONS

---

Waste should be disposed of in a landfill certified to accept such materials in accordance with federal, state, and local regulations.

---

### SECTION 14: TRANSPORTATION INFORMATION

---

D.O.T SHIPPING NAME:	Not applicable
HAZARD CLASS:	Non-regulated (for disposal purposes material is non-hazardous Class III regulated material)
ID NUMBER:	Not applicable
MARKING:	Not applicable
LABEL:	None
PLACARD:	None
HAZARDOUS SUBSTANCE/RQ:	Not applicable
SHIPPING DESCRIPTION:	Natural Stone products
PACKAGING REFERENCES:	None

---

### SECTION 15: REGULATORY INFORMATION

---

This product and/or its components have been previously introduced into U.S. commerce and is listed in the Toxic Substances Control Act (TSCA) Inventory of Chemicals in Commerce. Hence, it is subject to all applicable provisions and restrictions under TSCA 40 CFR Section 721 and 723.250.

# Safety Data Sheet:

## Natural Stone

FILE NO.: SDS.NATURALSTONE.01

SDS DATE: January 2024

Title 22 Division 2, California Code of Regulation Chapter 3 (Proposition 65): This product contains a chemical or chemicals known to the State of California to cause cancer and/or birth defects or other reproductive harm.

Title 8, Division 1, California Code of Regulation Chapter 4, Section 5204 (Cal-OSHA Emergency Temporary Standard for Silica): This product contains more than 10% crystalline silica. When performing a "high-exposure trigger task," follow Cal-OSHA's emergency temporary standard for silica. "High-exposure trigger task" includes machining, crushing, cutting, drilling, abrading, abrasive blasting, grinding, chiseling, carving, gouging, polishing, buffing, fracturing, intentional breaking, or intentional chipping of artificial stone as well as clean up, distributing, or handling of wastes, dusts, residues, debris, or other materials created during the above-listed tasks. Do not dry cut. Use one of the following wet cutting methods: (1) applying a constant, continuous, and appropriate volume of running water directly onto the surface of the stone; (2) submersing the stone underwater; or (3) water jet cutting using high pressure water to cut the stone. Wear a full face, tight-fitting powered-air purifying respirator or a respirator providing equal or greater protection equipped with a HEPA, N100, R100, or P100 filter. Use wet cleanup methods or vacuum cleaners equipped with a HEPA filter. Do not use compressed air on waste, dust, debris, residue, or other materials that may contain crystalline silica or on any surface or clothing or body surface that may contain crystalline silica.

STATE REGULATIONS: Crystalline silica as quartz (CAS: 14808-60-7)  
Massachusetts – Right To Know List  
New Jersey – Right to Know Hazardous Substance List  
Pennsylvania – RTK (Right to Know) List

This product or its components meets the following hazard definition(s) as defined by the Occupational Safety and Health Hazard Communication Standard (29 CFR Section 1910.1200):

- |   |   |   |
|---|---|---|
| <input type="checkbox"/> Combustible Liquid | <input type="checkbox"/> Flammable Aerosol                          | <input type="checkbox"/> Oxidizer       |
| <input type="checkbox"/> Compressed Gas     | <input type="checkbox"/> Explosive                                  | <input type="checkbox"/> Pyrophoric     |
| <input type="checkbox"/> Flammable Gas      | <input checked="" type="checkbox"/> Health Hazard (Sections 3 & 11) | <input type="checkbox"/> Unstable       |
| <input type="checkbox"/> Flammable Liquid   | <input type="checkbox"/> Organic Peroxide                           | <input type="checkbox"/> Water Reactive |
| <input type="checkbox"/> Flammable Solid    |   |   |

Based on information presently available, this product does not meet any of the hazard definitions of 29 CFR Section 1910.1200.

---

### SECTION 16: ADDITIONAL INFORMATION

---

#### GLOBAL HARMONIZATION IDENTIFICATION SYSTEM

GHIS: Health: 3 Fire: 4 Reactivity: 4

#### HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HMIS: Health: 0 Fire: 0 Reactivity: 0

#### NATIONAL FIRE PROTECTION ASSOCIATION

NFPA: Health: 0 Fire: 0 Reactivity: 0

PREPARATION INFORMATION: Date Prepared January 3, 2024