

Guardia and Guardia Pro, Usage & Care Instructions

Usage & Care Instructions

- Ensure you turn off floor heating before laying Guardia and Guardia Pro.
- Clean the underlying surface for better adhesion and to maximize reusage adhesion.
- The product should be laid down with an overlap of 4 in / 10 cm.
- Keep ambient temperature between 50-86 F / 10-30 C and humidity at less than 60%.
- Protect against direct sun exposure for prolonged periods of time.
- Ensure surfaces to be protected are dry before applying this product.
- Do not use on surfaces that have been treated with any solvent-based products before they have been properly cured per the manufacturer's guidelines and no longer emit solvent vapor.
- Avoid placing heavy objects directly on the surface protection mat for prolonged periods of more than 24 hours.
- Taping down the start and end of the rolls is recommended.
- To ensure clean removal and possible residual adhesive, this product should not be left on any unfinished surface for more than 60 consecutive days.
- This product can be thermally disposed of, where available.
- If the use and care of the product and environment has changed or caused adhesion to the floor surface it can be cleaned using a kitchen cloth, a small amount of neutral PH soap and lukewarm water. Using the product outside of the recommended usage and care conditions will void warranty and liability.
- Ensure floor heating is turned off when using Guardia.
- **GUARDIA IS NOT RECOMMENDED FOR CEMENT OR CONCRETE FLOORS.** The adhesive may leave residue and/or fail to adhere as effectively on cement surfaces due to it's high mineral and polymer content.