

Bronze Thimbles

Bronze Rope Thimbles are made from a high strength, noncorrosive, non-sparking nickel-aluminum bronze alloy.



Description

This rope thimble was developed primarily for use with nylon, manila, polypropylene, and Polyvinyl chloride ropes. Four rings or "keepers" secure the rope from jumping out of the thimble. Seventeen sizes are available in rope-diameters from 3/8" to 4-3/4".

Specifications

Rope Diameter (in)	Shackle Size (in)	A (in)	B (in)	C (in)	D (in)	G (in)	H (in)	T (in)	Weight (kg)
3/8" – 7/16"	3/8"	7/8"	1-1/2"	9/16"	3/4"	2-1/16"	2-7/16"	3/32"	0.20 lb
1/2" – 9/16"	3/8"	1"	1-5/8"	11/16"	29/32"	2-3/8"	2-13/16"	7/64"	0.40 lb
5/8"	1/2"	1-1/8"	2"	7/8"	1-1/8"	3-1/8"	3-1/2"	1/8"	0.60 lb
13/16" – 15/16"	5/8"	1-1/4"	2-5/16"	1-1/16"	1-3/8"	3-3/4"	4-3/16"	5/32"	0.90 lb
1"	3/4"	1-5/8"	2-3/4"	1-3/16"	1-9/16"	4-1/4"	4-11/16"	3/16"	1.60 lb
1-1/8" – 1-1/4"	7/8"	1-7/8"	3-1/16"	1-7/16"	1-27/32"	5-1/16"	5-3/16"	13/64"	2.10 lb
1-5/16"	7/8"	2-1/8"	3-5/8"	1-1/2"	1-15/16"	5-1/2"	5-13/16"	7/32"	2.60 lb
1-1/2"	1"	2-3/8"	4-1/16"	1-11/16"	2-5/32"	6-1/4"	6-1/2"	15/64"	3.70 lb
1-5/8"	1-1/8"	2-5/8"	4-1/2"	1-13/16"	2-5/16"	6-3/4"	7-1/16"	1/4"	4.80 lb
1-3/4"	1-1/4"	2-7/8"	4-15/16"	2"	2-17/32"	7-3/8"	7-3/4"	17/64"	6.80 lb
2"	1-1/4"	3-1/8"	5-3/8"	2-1/4"	2-13/16"	8-3/8"	8-5/8"	9/32"	7.70 lb
2-1/8"	1-3/8"	3-1/2"	5-13/16"	2-3/8"	2-31/32"	9" 9-1/8"	9-1/8"	19/64"	9.50 lb
2-1/4"	1-1/2"	3-7/8"	6-1/4"	2-1/2"	3-1/8"	9-3/8"	9-5/8"	5/16"	11.00 lb
2-5/8"	1-5/8"	4-3/8"	7"	2-7/8"	3-5/8"	10-5/8"	10-3/4"	3/8"	16.50 lb
2-3/4" – 2-7/8"	2"	4-7/8"	8"	3-1/4"	4-1/8"	11-3/4"	12-1/8"	7/16"	25.00 lb
3" – 3-1/4"	2"	5-3/8"	9-1/4"	3-1/2"	4-1/2"	13-1/8"	13-7/8"	1/2"	38.00 lb
3-3/4"	—	8"	10"	4"	5-3/8"	14-5/8"	15-1/2"	11/16"	60.00 lb
4-3/4"	—	9"	12-1/2"	6-3/8"	8-3/8"	22-7/8"	21-1/2"	1"	225.00 lb

* Not recommended for use with Class II ropes. Dimensions are approximate—within standard foundry practice.