## **River Guard**

A semi flexible braided Nylon cover that is coated with a proprietary polyurethane elastomer for enhanced abrasion resistance.



## Description

This chafe sleeve can either be affixed to your line at particular wear points, or can be a sliding chafe sleeve, to be positioned on differing wear points.

SWOS has committed substantial research and development resources to designing a line of chafe protection products that maximize the service life of our ropes. The result is a family of products perfectly suited to combat cutting and abrasion encountered in offshore, mooring, and tug operations. Because each application has its own unique requirements, SWOS has developed a full range of options to protect your investment and ensure the longest service life for your working ropes.

## Specifications

Size	Fits Rope Diameter		Covers Splice Diameter	
	Inches	mm	Inches	mm
Size E	1" - 1-3/4"	24 – 44mm	3/4" – 1"	18 – 24mm
Size F	1-7/8" – 2-1/4"	45 – 56mm	1-2/8" – 1-3/8"	28 – 34mm
Size G	2-3/8" - 3-1/4"	57 – 80mm	1-1/2" - 1-3/4"	36 – 44mm

	Size	Fits Rope Circumference		Covers Splice Circumference	
		Inches	mm	Inches	mm
	Size E	3" - 5-1/2"	72 – 132mm	2-1/4" - 3"	54 – 72mm
	Size F	5-5/8" – 7"	136 – 168mm	3-3/8" – 4-1/8"	84 – 102mm
	Size G	7-1/8" – 10"	174 – 240mm	4-1/2" - 5-1/4"	108 – 132mm





<sup>\*</sup> Larger sizes available upon request