

# Hawser Thimble

The cast-steel Heavy Duty Hawser Thimble is designed for use with high-performance class II synthetic fiber ropes such as AmSteel®-Blue, Force-8, and DPX™-75.



## Description

The galvanized thimble provides smooth and even grooves, maximum strength in critical areas, and the proper bending radius for the rope. When used with synthetic ropes, the thimble eye should be lashed at approximately 2, 4, 8, and 10 o'clock on the thimble circumference to secure it to the rope when not in service.

## Specifications

Rope Diameter (in)	A (in)	B (in)	C (in)	D (in)	E (in)	F (in)	Weight (lbs)
5/8 - 3/4	6-7/8	4-1/2	5	3	1-3/16	13/32	3-1/2
7/8 - 1	8-5/8	5-3/4	6-1/4	3-3/4	1-7/16	17/32	6
1-1/8 - 1-1/4	10-1/8	6-3/4	7-1/4	4-1/4	1-11/16	21/32	9-1/2
1-3/8 - 1-1/2	12-1/8	8	8-3/4	5	2-3/16	25/32	18-1/2
1-5/8 - 1-3/4	12-3/4	8	9-1/4	5	2-7/16	15/16	24
2	14-3/4	9-1/2	10-3/4	6	2-11/16	1-1/16	33-1/2
2-1/8 - 2-1/4	17-1/8	11	12-1/2	7	3-1/8	1-3/16	53-1/2
2-1/2	19-1/4	12-3/4	14-1/4	8-1/8	3-7/8	1-3/8	81-1/2
3	24-1/2	15	17	9-3/8	4-15/16	1-5/8	136-1/2
3-1/2	30	19-1/2	20	11-1/2	5-1/2	1-7/8	216-1/2

\* Dimensions in accordance with Standard Foundry Practice.