


Quik-Splice™



In this fast splicing, 12-strand single braid construction, high-strength Ultra Blue fiber creates a rope that is 30-35% higher in strength than the equivalent polypropylene construction, Quik-Splice - to 3 times more wear life than polypropylene.

Description

Product Code:
335

Fiber (Core/Cover):
Ultra Blue Polyolefin

Specific Gravity:
0.94 (floats)

Splice:
Product Specific Class I

Manufacturer:
Samson Rope Technologies, Inc.

Features

- 30-35% stronger than standard polypropylene
- Abrasion resistant, especially in wet environments
- Easy to splice
- UV stabilized
- Water resistant

Applications

- Accessory Product / Recreational Marine
- Block Line
- Hand Line
- Other Fishing Line
- Pulling / Stringing Line
- Purse Seine Line

Quik-Splice™

Specifications

Diameter (in)	Circum. (in)	Weight per 100 ft. (lbs.)	Average Strength (lbs)	Minimum Strength (lbs)	Diameter (mm)	Circum. (mm)	Weight per 100M	Average Strength (kg)	Minimum Strength (kg)
1/4	3/4	1.1	1,400	1,300	6	18	1.6	640	570
5/16	1	1.7	2,500	2,300	8	24	2.5	1,100	1,000
3/8	1-1/8	2.7	3,500	3,200	9	27	4.0	1,600	1,400
7/16	1-1/4	3.5	4,600	4,100	11	33	5.2	2,100	1,900
1/2	1-1/2	4.9	6,700	6,000	12	36	7.3	3,000	2,700
9/16	1-3/4	6.0	7,500	6,800	14	42	8.9	3,400	3,100
5/8	2	8.0	10,900	9,800	16	48	11.9	4,900	4,400
3/4	2-1/4	9.9	13,000	11,700	18	54	14.7	5,900	5,300
7/8	2-3/4	15.2	16,000	14,400	22	66	22.6	7,300	6,500
1	3	21.0	23,100	20,800	24	72	31.2	10,500	9,400
1-1/8	3-1/2	24.5	28,600	25,700	28	84	36.5	13,000	11,700
1-1/4	3-3/4	29.0	31,300	28,200	30	90	43.2	14,200	12,800
1-1/2	4-1/2	41.0	43,800	39,400	36	108	61.0	19,900	17,900
1-5/8	5	51.1	55,000	49,500	40	120	76.0	24,900	22,500
1-3/4	5-1/2	60.0	63,800	57,400	44	132	89.3	28,900	26,000
2	6	70.0	76,300	68,700	48	144	104	34,600	31,100
2-1/8	6-1/2	84.0	88,800	79,900	52	156	125	40,300	36,300
2-1/4	7	98.0	102,000	91,800	56	168	146	46,300	41,600
2-1/2	7-1/2	114	113,000	102,000	60	180	170	51,300	46,100

* Specifications are for spliced strengths.

Sizes 7/16" (11 mm) and below changes from 12-strand to 8-strand or 16-strand construction.