


Sling Shackle

Bow shackles with safety bolt.



Certification

At no extra charge, this product can be supplied with a works certificate, 3.1 material certificate, manufacturer test certificate, EC declaration of Conformity and all shackles from 75 T and up are supplied with a Lloyd's Register of Shipping Certificate on proof load. For shackles 75 T and up an MPI and/or US inspection certificate can be supplied on request.

Material:
Bow and pin alloy steel, Grade 8, quenched and tempered

Safety Factor:
MBL equals 5 x WLL

Finish
Shackle bow painted silver, pin painted green

Temperature:
-20 °C up to +200 °C

Specifications

Working Load Limit (t)	Diameter Body a (mm)	Diameter Pin b (mm)	Diameter Eye c (mm)	Width Eye d (mm)	Width Inside e (mm)	Length Inside f (mm)	Width Bow g (mm)	Length h (mm)	Length Bolt i (mm)	Width j (mm)	Thickness Nut k (mm)	Bearing Surface l (mm)	Weight Each (kg)
40	55	51	109	45	84	199	140	331	252	235	38	97	21
55	60	57	115	55	90	240	160	389	294	270	45	100	30
75	68	70	125	54	110	290	185	473	327	317	54	120	48
125	85	80	154	85	137	366	220	583	426	390	64	150	92
150	94	95	179	89	147	391	253	645	435	434	50	170	140
200	110	105	199	100	158	481	280	759	470	482	50	205	205
250	126	120	227	110	179	542	300	859	519	530	60	240	264
300	135	134	245	122	195	601	350	947	575	620	70	265	360
400	160	160	293	145	231	576	370	985	675	690	80	320	580
500	170	180	328	160	263	681	450	1131	748	790	90	339	780
600	190	200	348	170	289	741	490	1234	809	865	100	370	980
700	200	215	392	190	315	751	540	1284	879	901	100	400	1360
800	218	230	420	200	342	851	554	1426	942	947	110	420	1430
900	242	255	466	220	368	851	580	1488	1023	1023	120	440	1650
1000	260	270	490	240	399	851	614	1532	1103	1107	120	460	2970
1250	285	300	510	260	452	931	650	1666	1227	1182	150	530	3700
1550	285	320	550	280	483	950	680	1710	1300	1253	150	560	4000

* ±5% forging tolerance on inside width and length

