

CP30 Construction Pup



30- or 40-ton capacities → Stockpile or windrow → Watertight; no leaks → Low load height




CP30 Construction Pup

CP30 SmithCo Side Dump Trailer 20-ton model also available.

	20 torrilloder diso dvalidble.
Frame Length	30' 9"
Tub Length	21'
Width	10' (120")
Loading Height	8'
Towing Eye	Side Oscillating, 2" Drawbar Pin, 360 degree rotation
Safety Chains	1/2" Safety Chains w/ Safety Hooks
Tub Construction	1/4" Thick, Steel (or equivalent) AR 400 Round Floor Style Tub
Frame Construction	80/100 KSI, Fabricated Steel I-Beam
Landing Gear	High Clearance
Cylinders	3500 PSI, 5" Bore
Hinges	Self-Aligning, Spherical Bearing Type (greaseable)
Suspension	90K Single Point Walking Beam
Axles	30,000# Capacity
Hubs	10 Hole, Hub Piloted
Drums	Outboard Mount, Cast Steel
Brakes	Hydraulic and Air Available
Wheels	Tubeless, Steel Disc
Tires	750/45 R 22.5 LGP (std)
Lights	12 Volt LED ICC w/Sealed Harness
Paint	Polyurethane, any combination of gray, white or black Special colors available upon request
Min. Tractor Hydraulic Reqs.	25-30 GPM, 2,600-2,800 PSI, 10 Gallon Reservoir
Net Payload Rating	30 tons

CP30 Tub Capacities

	30-ton Tub
Waterfull	15 cu yd
Heaped	22 cu yd (Bolt On Extensions to 49 cu yd available)



Model CP30

