



SX3

Three Axle Side Dump Trailer



37' to 50' frame lengths ◀ Stockpile or windrow ▶ Watertight; no leaks ▶ Low load height

800-779-8099 • 712-546-4409 • sidedump.com

Three Axle Side Dump
SX3



SX3

Three Axle Side Dump Trailer

Model SX3-4234 SmithCo Side Dump Trailer

Specs shown are for 41'5" frame length; other configurations available.

Frame Length	41' 5"
Tub Length	34'
Width	102'
Height	8' 3" at Tub side, 9' 6" at Center
Tub Construction	1/4" Thick, AR400 Steel (or equivalent) 3/16" Thick, AR400 Steel (or equivalent) is optional External Column Supports, No Center Tub Divider
Frame Construction	80/100 KSI, Fabricated Steel I-Beam
Kingpin	2" Kingpin, 18" Setting, Replaceable Type
Landing Gear	Two Speed, Non-Load Bearing
Bumper	Push Bar Type, Bolt-On
Cylinders	3500 PSI, 5" bore
Hinges	Self-Aligning, Spherical Bearing Type (greaseable)
Suspension	Air Ride Suspension Standard; Spring Ride Available
Axles	(3) 25,000# capacity
Hubs	10 Hole, Hub Piloted
ABS	2S1M Anti-Lock Brake System
Drums	Outboard Mount, Cast Steel
Wheels	Steel Disc, 8.25 x 22.5 (12)
Tires	11 R 22.5 G Radial Tires (12)
Brakes	16 1/2" x 7"
Fenders	Front & Rear, 1/4" Synthetic, 7 Degree Slope
Lights	12 Volt LED ICC w/Sealed Harness
Mud Flap	(2) Polyline Anti-Spray Splash Guard w/SmithCo name
Paint	Polyurethane, any combination of gray, white or black Special colors available upon request
Min. Tractor Hydraulic Reqs.	25-30 GPM, 2,600-2,800 PSI, 10 Gallon Reservoir

SX Series Tub Capacities

	34' Tub	36' Tub
Waterfull	23 cu yd	24 cu yd
Heaped	31 cu yd	32 cu yd

