



SX2

Tandem Axle Side Dump Trailer



30' to 42' frame lengths ◀ Stockpile or windrow ▶ Watertight; no leaks ▶ Low load height

800-779-8099 • 712-546-4409 • sidedump.com

SX2

Tandem Axle Side Dump



SX2

Tandem Axle Side Dump Trailer

Frame Length	39' 5"
Tub Length	34'
Width	8' 6"
Height	8' 3" at Tub side, 9' 6" at Center
Tub Construction	1/4" Thick, AR450 Steel (or equivalent) 3/16" Thick, AR450 Steel (or equivalent) is optional External column supports, no center tub divider
Frame Construction	80/100 KSI, Fabricated Steel I-Beam
Kingpin	2" Kingpin, 18" Setting, Replaceable Type
Landing Gear	Two Speed, Non-Load Bearing
Bumper	Push Bar Type, Bolt-On
Cylinders	3500 PSI, 5" bore
Hinges	Self-Aligning, Spherical Bearing Type (greaseable)
Suspension	Air Ride; Four Spring & others optional
Axles	(2) 25,000# capacity
Hubs	10 Hole, Hub Piloted
ABS	2S1M Anti-Lock Brake System
Drums	Outboard Mount, Cast Steel
Wheels	Steel Disc, 8.25 x 22.5 (8)
Tires	11 R 22.5 G Radial Tires (8)
Brakes	16 1/2" x 7"
Fenders	Front & Rear, 1/4" Synthetic, 7 Degree Slope
Lights	12 Volt LED ICC w/Sealed Harness
Mud Flap	(2) Polyline Anti-Spray Splash Guard w/SmithCo name
Paint	Polyurethane, any combination of gray, white or black Special colors available upon request
Min. Tractor Hydraulic Reqs.	25-30 GPM, 2,600-2,800 PSI, 10 Gallon Reservoir

SX Series Tub Capacities

	34' Tub	36' Tub
Waterfull	23 cu yd	24 cu yd
Heaped	31 cu yd	32 cu yd

