



Product Schedule 40 Plain End Solid Wall ABS DWV Pipe

Project Information

JobName: _____ Date Submitted: _____
 Location: _____ Submitted by: _____
 Engineer: _____ Approved by: _____
 Contractor: _____ Manufacturer's Rep: _____

Application Information

For use for DWV applications only

Technical Data

Materials

Acrylonitrile Butadiene Styrene

Pressure Ratings

DWV Only

Temperature Ratings

Max Operating Temperature - 140°F

Codes

Universal Plumbing Code (UPC®)

International Plumbing Code (IPC®)

Standards

ASTM D2661

Listings

IAPMO 10897

	Pipe Size	Part Number	Dimensions			Pieces Per Lift
			O.D. (IN)	Nom Pipe Size (IN)	Weight (LBS)	
<input type="checkbox"/>	1-1/2"X10'	29-1510SW	1.900	1-1/2	3.6	259
<input type="checkbox"/>	1-1/2"X20'	29-1520SW	1.900	1-1/2	7.2	259
<input type="checkbox"/>	2"X10'	29-210SW	2.375	2	5	167
<input type="checkbox"/>	2"X20'	29-220SW	2.375	2	10	167
<input type="checkbox"/>	3"X10'	29-310SW	3.5	3	10	75
<input type="checkbox"/>	3"X20'	29-320SW	3.5	3	20	75
<input type="checkbox"/>	4"X10'	29-410SW	4.5	4	14	48
<input type="checkbox"/>	4"X20'	29-420SW	4.5	4	28	48
<input type="checkbox"/>	6"X10'	29-610SW	6.625	6	26	20
<input type="checkbox"/>	6"X20'	29-620SW	6.625	6	52	20

