



Product Schedule 40 Plain End Cellular Core ABS DWV Pipe

Project Information

Job Name: _____	Date Submitted: _____
Location: _____	Submitted by: _____
Engineer: _____	Approved by: _____
Contractor: _____	Manufacturer's Rep: _____

Application Information

For use for DWV applications only.

Technical Data

Materials

Acrylonitrile Butadiene Styrene

Pressure Ratings

DWV Only

Temperature Ratings

Max Operating Temperature: **140°F**

Codes

Universal Plumbing Code (UPC®)

National Plumbing Code of Canada

Standards

ASTM F628

Listings

IAPMO 10434

Dimensional Information

	Pipe Size	Part Number	Dimensions			Pieces Per Lift
			O.D. (in)	Nom. Pipe Size (in)	Weight (lbs)	
	1-1/2"×10'	29-1510	1.900	1.5	2.70	259
	1-1/2"×20'	29-1520	1.900	1.5	5.40	259
	2"×10'	29-210	2.375	2	3.70	167
	2"×20'	29-220	2.375	2	7.40	167
	3"×10'	29-310	3.5	3	7.45	75
	3"×20'	29-320	3.5	3	14.90	75
	4"×10'	29-410	4.5	4	10.71	48
	4"×20'	29-420	4.5	4	21.42	48
	6"×10'	29-610	6.625	6	18.78	20
	6"×20'	29-620	6.625	6	37.56	20

