



The Flowmaster powered fresh air breathing apparatus is designed to provide a constant flow of air for 1 or 2 users working in noxious environments, such as gas, by drawing air from a nearby fresh, uncontaminated source.

**FLOWMASTER** 

The Flowmaster is ideal for confined spaces, gas, utility, tank storage and other oxygen-poor or hazardous work environments where the air may be unsafe.

Certified to EN 138: 1994, the Flowmaster was developed by Tower Supplies and Luno Systems for a major gas DNO requiring a Quick Connect / Release system that was versatile, quick and easy to use, and wanting a better, more practical, up-to-date, lightweight solution.

"SGN fully support and recommend the Flowmaster powered FABA system as a convenient, easy-to-use, flexible, modern and reliable system that is now being rolled out within our business. With our previous system discontinued by the manufacturer, and limited alternatives available, SGN appreciated being able to provide input into designing the Flowmaster system and look forward to further developments."



Gary Powell Safety, Health and Environment Manager, SGN

...work safer, be better.



Key Features & Benefits



Fall protection harness approved to EN361 with strain relief for hose

Perfect for excavation work



Lightweight waistbelt

- Increased comfort
- Also available with shoulder harness



Certified to EN138:1994



Optional Quick Connect and Release

- Provides leak tight seal
- Easy connect
- Quick and easy release in emergencies



Approved for Flowmaster EN136 mask

- Wide field of vision
- Superior user comfort
- Range of sizes to ensure good fit
- Compatible with a range of masks



Hose length options and reels

- More comfortable breathing reducing fatigue
- Unlimited air source no time restrictions

Designed and Manufactured in the UK

The Flowmaster FABA system includes:

Blower unit with 3m power cable; Flowmaster full face mask and bag; Superlite waistbelt; 10m air hose; male and female Quick connect couplings; Kit bag. [Product code: D07.11273]

Full range of accessories, consumables, spares and replacements available including FR hood, FR hose covers, mask wipes

...work safer, be better.



**70We**R

Specifications



	Electrical Connection	110v 16A
	Dimensions	190 x 270 x 190mm
	Weight	5.5kg
7	Flowrate	Min 120lpm
	Protection	IP64
	Hose Length	Up to 60m
	Hose Material	PVC
	Approved Standard	EN 138
	Number of Users	1 or 2

**Options** 

Fan Unit	Hose	Connector	Harness	Mask
Flowmaster 1 110v mains supplied fan unit. Optional gas detector bracket	10m, 30m, 60m Hose reel	Standard thread  Quick connect/ release	Integrated EN361 fall protection harness  Comfort shoulder harness  Superlite belt	EN136 full face mask, small, medium, large

## Coming soon:

Flowmaster 2 with re-chargeable battery, status displays and warning features for battery, flow rate and blocked filters.

Plus intrinsically safe ATEX version e.g. for hydrogen networks

Video - How to use and maintain the Flowmaster FABA System.



...work safer, be better.

